

# FST-18H



## FTTx Active Cladding Alignment Fusion Splicer

Auto splice mode manifest user-friendly design

Dust-proof, water-proof, high-temperature resistance, adapting to various altitude and formidable nature conditions

4.3" high resolution color LCD touch screen, 380X magnification, visible clearly with bare eyes

Packed with detachable 4800mAh battery, more than 230 times of splicing and heating

3 high-power white LEDs and illuminated keypads simplifies your work at night

Detachable multifunction fixture, suitable for various fiber type

German CNC technique and integrated fiber-adjust frame, which make performance much stable

Built-in Japanese components and Korean chipset



3s Turn On



6s Fast Splicing



13s Heating

**STABLE  
INTELLIGENT  
ECONOMIC  
CONVENIENT**

Priority model for FTTx



# Splicer Master **FST-18H**

## Active Cladding Fusion Splicer

Combining domestic with foreign technologies, Tumtec has been dedicated to providing professional optical fiber solution and become the renowned fusion splicer & fiber cleaver manufacturer for 15 years.



Standard Accessories
Fusion splicer FST-18H*1
Fiber cleaver*1
Battery*1
Power adapter*1
AC power line*1
Back-up electrode*1
Cooling tray*1
Carrying case*1
Carrying strap*1
User manual*1
Splicing test report*1
Fiber stripper*1
Drop cable stripper*1
Alcohol bottle*1

Equipment Parameters	
Model	FST-18H
Dimension	115W*160L*135H (excluding rubber bumper) / 120W*165L*135H (including rubber bumper)
Weight	1735G (with battery) / 1355G (without battery)
Number of Fiber	Single
Applicable Fibers	SM(ITU-T G.652& G.657A, B)/MM(ITU-T G.651)/DS(ITU-T G.653)/NZDS(ITU-T G.655)
Compatible Fiber/Cable	0.25 - 3.0mm/Indoor Cable/ drop cable (flat type)
Cleaved Length	Diameter: 100 - 1000μm/Cleave Length: 8-16mm
Cladding Diameter	80 - 150 μm
Splicing Mode	Pre-set 41 splicing modes, max 100 modes (editable by user)
Heating Mode	Pre-set 5 heating modes (20/30/40/50/60mm), max 100 modes (editable by user)
Typical Splice Loss	SM: 0.03dB / MM: 0.02dB/ DS: 0.05dB / NZDS: 0.05 dB/ G.657: 0.03dB (ITU-T Standard)
Return Loss	>60dB
Lighting	3 White LEDs
Splicing Time	Quick mode: 6s
Estimated Splice Loss	Available
Heating Time	Quick heating time: 13s, typical heating time: 30s, adjustable for protection sleeve size 20 - 60mm
Results Storage	20000 latest records & 200 images
Tension Test	1.96 - 2.25N
Operating Condition	Operating Altitude: 0 - 5000m above sea level, 0 - 95% relative humidity, - 20 ~ + 55 °C, Max Wind 15m/s
Storage Condition	0 ~ 95% relative humidity, -40 ~ 80 °C
Display	90° bi-directional view, 4.3" Color High Resolution LCD monitor
Fiber View & Magnification	X, Y, XY, X/Y: 380X Magnification
Power Supply	AC Input 100 - 240V 50Hz DC Input 12 - 15V
No. of Splice/Heating with Battery	4800mAh Battery Capacity, Typical 230 times (Splice + Heat)
Operating Methods	Button/Touch Screen
Automatic Calibration	Automatic arc calibration by air pressure and temperature
Electrode Life	5000 arcs
Terminal	Mini USB 2.0

Tumtec reserve the right to change the design, properties and products without notice. 2019 print in China



Guangdong Tumtec Communication Technology Co., Ltd

Website: [www.gdtumtec.com](http://www.gdtumtec.com) / [www.tumtecchina.com](http://www.tumtecchina.com) Email: [enquiry@tumtec.com](mailto:enquiry@tumtec.com) Telephone: (+86)757-63509010  
Address: Rm 302-1, A5 building Hantian Hi-tech Zone, 17th Shenhai Road, Guicheng Avenue,  
Nanhai district, Foshan, Guangdong, China.